PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION



(21) Interi (22) Interi (30) Priori	C 5/02, C12S 3/08 // D21C 9/1 national Application Number: national Filing Date: 23 November	PCT/DK94/00 per 1994 (23.1)	(4	(81) Designated States: AM, AU, BB, B	1 June 1995 (01.06.95
(22) Interi (30) Priori			0437	(81) Designated States: AM, AU, BB, B	G. BR. BY. CA. CN C
N() (D) (T2) Inven (75) Inven (I) M: (I) ke Y2	23 November 1999 cant (for all designated States excording Royal Allé, I DRDISK A/S [DK/DK]; Novo Allé, I K).	ept US): NO DK-2880 Bags GHARYO, Ma 65-1, Yatsuga IIMOTO, Hide nabashi-shi, Cl i [IP/IP]; 1163 hiba-ken 267 (DK OVO værd asaki saki, esato hiba- 5-31, JP). Cor-	EE, FI, GE, HU, JP, KE, KG, K LV, MD, MG, MN, MW, NO, N SK, TJ, TT, UA, US, UZ, VN, 1 CH, DE, DK, ES, FR, GB, GR, SE), OAPI patent (BF, BJ, CF, C MR, NE, SN, TD, TG), ARIPO p Published With international search report.	P, KR, KZ, LK, LR, L' NZ, PL, RO, RU, SD, S European patent (AT, Bl IE, IT, LU, MC, NL, P G, CI, CM, GA, GN, MI
(57) Abstr In th	act e production of pulp and paper from	starch-coated	paper	TH STARCH DEGRADING ENZYME E. t, the deinking effect can be improved by in t. The process comprises enzyme treatment	ncluding a treatment wi

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

Austria	GB	United Kingdom	MR	Mauritania
Australia	GE	Georgia	MW	Malawi
Barbados	GN	Guinea	NE	Niger
Belgium	GR	Greece	NL	Netherlands
Burkina Faso	HU	Hungary	NO	Norway
Bulgaria	IR.	Ireland	NZ	New Zealand
Benin	IT	Italy	PL	Poland
Brazil	JP	Japan	PT	Portugal
Belarus	KE	Kenya	RO	Romania
Canada	KG	Kyrgystan	RU	Russian Federation
Central African Republic	KP	Democratic People's Republic	SD	Sudan
Congo		of Korea	SE	Sweden
Switzerland	KR	Republic of Korea	SI	Slovenia
Côte d'Ivoire	KZ	Kazakhsian	SK	Slovakia
Cameroon	LI	Liechtenstein	SN	Senegal
China	LK	Sri Lanka	TD	Chad
Czechoslovakia	LU	Luxembourg	TG	Togo
Czech Republic	LV	Latvia	TJ	Tajikistan
-	MC	Monaco	· TT	Trinidad and Tobago
Denmark	MD	Republic of Moldova	ŪA	Ukraine
Spain	MG	Madagascar	US	United States of America
Finland	ML	Mali	UZ	Uzbekistan
-	MN		VN	Vict Nam
Gabon		•		
	Australia Barbados Belgium Burkina Faso Bulgaria Benin Brazil Belarus Canada Central African Republic Congo Switzerland Côte d'Ivoire Cameroon China Czechoslovakia Czech Republic Germany Denmark Spain Finland France	Australia GE Barbados GN Belghum GR Burkina Faso HU Bulgaria IE Benin IT Brazil JP Belarus KE Canada KG Central African Republic KP Congo Switzerland KR Côte d'Ivoire KZ Cameroon LI China LK Czechoslovakia LU Czech Republic LV Germany MC Denmark MD Spin MG Finland ML France MN	Australia GE Georgia Barbados GN Guinea Belghum GR Greece Burkina Faso HU Hungary Bulgaria IR Ireland Benin IT Italy Brazil JP Japan Belarus KE Kenya Canada KG Kyrgystan Central African Republic KP Democratic People's Republic Congo of Korea Switzerland KR Republic of Korea Côte d'Ivoire KZ Kazakhstan Cameroon LI Liechtenstein China LK Sri Lanka Czechoslovakia LU Luxembourg Czech Republic LV Latvia Germany MC Monaco Demnark MD Republic of Moldova Spain MG Madagascar Finland MI Mali France MN Mongolia	Australia GE Georgia MW Barbados GN Guinea NE Belghum GR Greece NL Burkina Faso HU Hungary NO Bulgaria IE Ireland NZ Benin IT Italy PL Brazil JP Japan PT Belarus KE Kenya RO Canada KG Kyrgystan RU Central African Republic KP Democratic People's Republic SD Congo of Korea SE Switzerland KR Republic of Korea SI Côte d'Ivoire KZ Kazakhstan SK Cameroon LI Liechtenstein SN China LK Sri Lanka TD Czechoslovakia LU Luxembourg TG Czech Republic LV Latvia TJ Germany MC Monaco TT Demnark MD Republic of Moldova UA Spain MG Madagascar US Finland ML Mali UZ France MN Mongolia

WO 95/14807 PCT/DK94/00437

Deinking of waste paper by treatment with starch degrading enzyme e.g. amylase

TECHNICAL FIELD

This invention relates to processes for producing a papermaking pulp and producing new paper from old starch-coated printed paper. More particularly, 5 it relates to such processes with improved ink removal leading to improved brightness of the pulp or paper.

BACKGROUND ART

In the recycling of old starch-coated printed paper such as old newspapers and magazines for use in papermaking, it is usually desirable to remove the printing ink in order to produce new paper of high brightness. It is therefore conventional to repulp (or disintegrate) the old paper together with deinking chemicals, such as deinking surfactant, NaOH and sodium silicate, followed by bleaching with hydrogen peroxide and deinking chemicals and by separation of ink particles from the pulp.

A number of documents in the prior art describe the use of enzymes to improve ink removal. Thus, Japanese laid-open patent application Kokai Sho 59-9299 (Kao), Japanese laid-open patent application Kokai Sho 63-59494 (Honshu Paper), Japanese laid-open patent application Kokai Hei 2-80683 (Oji Paper) and WO 91/14819 (Novo Nordisk) describe the use of a cellulase, i.e. an enzyme acting on the cellulose fibers of paper. Japanese laid-open patent application Kokai Hei 2-160984 (Novo Nordisk) and Japanese laid-open patent application Kokai Hei 2-80684 (Lion) describe the use of a lipase, i.e. an enzyme acting on triglycerides in the printing ink.

It is the object of this invention to provide an improved process for 25 removal of printing ink for use in the recycling of old starch-coated paper.

10

STATEMENT OF THE INVENTION

Surprisingly, we have found that in the production of pulp and paper from starch-coated paper, the deinking effect can be improved by including a treatment with a starch-degrading enzyme.

Accordingly, the invention provides a process for producing a papermaking pulp from starch-coated printed paper, comprising the following steps:

- a) disintegrating the paper to produce a pulp,
- treating with a starch-degrading enzyme before, during or after step a), and
- c) separating ink particles from the pulp after steps a) and b).

The invention also provides a process for recycling old starch-coated printed paper into new paper, comprising producing a pulp by the above process, followed by papermaking.

DETAILED DESCRIPTION OF THE INVENTION

15 Starch-coated printed paper

The process of the invention is applicable to the recycling of any kind of printed, starch-coated paper. Typical examples are old newspaper, magazines and printed stationery. The paper may contain mineral fillers such as calcium carbonate and clay.

The starch coating may consist of starch from any source and generally contains 20-30% of amylose and the balance amylopectin. Typical examples are corn starch, wheat starch, potato starch, rice starch and tapioca starch. Starch to be used as a coating material will generally be pretreated to achieve a limited hydrolysis by cooking with amylase or acid.

The starch coating may also consist of modified starch. Modified starches useful for paper coating include dextrin (e.g. white dextrin, canary dextrin

or British gum), acid-modified starch, oxidized starch (chlorinated starch), hydrozyethylated starch and cationic starch

The inks to be removed by the process of this invention include but are not limited to non-contact laser inks, xerographic toners, letterpress ink generally used in printing newsprint, magazine print, offset printing ink, ultraviolet or electron beam cured ink.

Disintegration

The disintegration step may be done in a conventional pulper, typically for 5-30 minutes at 3-30% pulp consistency. If the enzyme treatment is completed 10 before the disintegration, conventional deinking chemicals can be used in the disintegration.

Conventional deinking chemicals typically comprise an alkaline reagent and a surfactant. The surfactant can, e.g., be used at a dosage of 0.2-0.6%. The surfactant is preferably nonionic, e.g. ethoxylated octyl or nonyl phenol or any of the nonionic surfactants disclosed in Park et al., 1992, Biotechnology and Bioengineering 39:117-120. The alkaline reagent may be NaOH (e.g. 0.2-5%) and/or sodium silicate (e.g. 0.4-5%). The alkaline reagents are usually added to a pH of 8-12. The deinking chemicals may further comprise magnesium sulfate, an organic solvent such as kerosene, and sodium sulfite.

If the enzyme treatment is done during or after the disintegration, it may be preferable to modify the addition of deinking chemicals (as described further below) in order to provide suitable conditions for the action of the enzyme, and particularly to reduce or avoid the addition of alkaline reagent to achieve a pH which is suitable for the enzyme action.

25 Starch-degrading enzyme

20

The starch-degrading or amylolytic enzyme is preferably an amylase, e.g. an α -amylase, a glucoamylase or a debranching enzyme. A single enzyme or a combination may be used, e.g. α -amylase together with glucoamylase and/or a debranching enzyme. It is preferred to carry out the enzyme treatment at an alkaline

pH in the range 6-10, preferably 8-10 and to use an enzyme which is alkaline stable and active in this range and preferably has optimum activity in this range.

Examples of preferred α-amylases are those derived from strains of Bacillus, e.g. B. amyloliquefaciens (B. subtilis), B. licheniformis or B. stearothermophilus and from strains of Aspergillus, e.g. A. oryzae. Examples of commercial products are BANTM, Termamyl^{*}, Aquazyme UltraTM and FungamylTM (products of Novo Nordisk A/S).

Glucoamylase derived from a strain of Aspergillus niger is preferred, e.g. the commercial product AMG (product of Novo Nordisk).

The debranching enzyme is preferably a pullulanase, particularly one derived from a strain of *Bacillus acidopullulyticus*, e.g. the commercial product Promozyme[®] (product of Novo Nordisk).

The process conditions are selected so as to increase the brightness of the pulp after the deinking and the brightness of the new paper. Suitable conditions for *Bacillus* amylase may be pH 4-10, 20-90°C, preferably pH 6-10, 40-70°C. Suitable conditions for *A. oryzae* amylase may be pH 3-8, 20-70°C. A suitable reaction time may be found in the range 10 min - 24 hours, particularly 10 min - 3 hours at an amylase dosage of 0.01-10 KNU/g dry matter (1 KNU = 1000 NU, unit defined in US 4,933,279), preferably 0.03-3 (or 0.06-6) KNU/g of dry matter.

Optionally, one or more other enzymes, such as lipase, cellulase, protease and/or hemicellulase, can be used together with the starch-degrading enzyme to further improve the deinking efficiency.

Stirring may optionally be used during the enzymatic treatment.

Enzyme treatment

As stated above, the enzyme treatment may be done before, during or after the disintegration, and these alternatives will now be discussed.

Enzyme treatment before disintegration

The treatment with a starch-degrading enzyme can be done before the disintegration, e.g. by soaking the paper, either as it is or after shredding or cutting, so in an aqueous solution of the starch-degrading enzyme. The bath ratio (i.e., the

weight ratio of the enzyme solution to the paper) is preferably above 10, and the enzyme treatment is preferably done in the presence of a surfactant. In the case of an α -amylase from *Bacillus* it is preferred to add alkaline reagents (typically NaOH and sodium silicate) to achieve a suitable pH, e.g. pH 8-10 (preferably 8-9).

5 Preferably, the enzyme treatment is followed by additional separation of ink particles before the disintegration. The subsequent disintegration may be done in a conventional manner in the presence of deinking chemicals.

The disintegration may be followed by conventional bleaching with hydrogen peroxide and deinking chemicals before the ink separation. Preferably, 10 separation of ink particles is done both before and after the bleaching.

Enzyme treatment during disintegration

Alternatively, the enzyme treatment may be done during the disintegration. In this case, the enzyme treatment may optionally be continued by holding the pulp after the disintegration.

The enzyme treatment is preferably done in the presence of a surfactant, and in the case of an α-amylase from *Bacillus* it is preferred to add alkaline reagents (typically NaOH and sodium silicate) to achieve a suitable pH, e.g. pH 8-10 (preferably 8-9).

The disintegration and enzyme treatment may be followed by 20 conventional bleaching with hydrogen peroxide and deinking chemicals before the ink separation. Preferably, separation of ink particles is done both before and after the bleaching.

Enzyme treatment after disintegration

The enzyme treatment may be done by adding enzyme to the pulp after disintegration. In a preferred embodiment, this is done simultaneously with hydrogen peroxide bleaching, preferably in the presence of a surfactant. In the case of simultaneous bleaching and treatment with an α-amylase from *Bacillus*, it is preferred to add 0.5-2% H₂O₂ and alkaline reagents (typically NaOH and sodium silicate, e.g. 1-5% sodium silicate and 0.5-5% NaOH) so as to achieve pH 9-10. The

combined bleaching and enzyme treatment is preferably done at 30-60°C for 1-3 hours.

Separation of ink particles

After the disintegration and enzyme treatment, ink particles may be separated from the pulp in a conventional manner, such as by mechanical deinking, flotation, chemi-mechanical deinking, agglomeration chemistry (see e.g. McBride, Pulp and Paper, April 1994, Miller Freeman Publishers, San Francisco, p. 44), washing, cycles of dilution and filtration, treatment in hydrolcyclones, or by a suitable combination of these.

10 Papermaking

After deinking according to the invention, the deinked pulp is generally mixed with other pulp, e.g. kraft pulp and mechanical pulp etc., before papermaking. The final papermaking step can be done in a conventional papermaking machine.

EXAMPLES

15 EXAMPLE 1

Enzyme treatment before disintegration with deinking chemicals

Two kinds waste paper were treated by the process of the invention:

Printed fine paper, mainly containing kraft pulp, off-set printed, starch coated, 8 months aged. Japanese regular newspaper containing deinked pulp, mechanical pulp, kraft pulp etc., off-set printed, starch coated, 4 months aged at room temperature.

10 g of the waste paper was cut by a shredder, suspended in water at 1% concentration, 65°C, pH 7.2. α-amylase (Aquazyme Ultra) was added in an amount of 0.3 KNU/g paper, and the mixture was kept for 60 minutes without 25 agitation.

Rinsing was done with 2 I of water, twice.

Disintegration was done in a laboratory mixer for disintegration of paper at 4% pulp concentration, 55°C for 10 minutes with the following deinking chemicals: 0.3% of surfactant (Liptool 160H, product of Nikka Kagaku KK, Japan), 0.5% NaOH and 0.8% sodium silicate.

5 Washing was done with 21 of water, twice.

A paper sheet was made on an 80 mesh wire (16 cm diameter).

A control experiment was done by the same procedure, but without the enzyme treatment.

Brightness of the paper sheet was measured at 457 nm in a spectrophotometer equipped with an integrating sphere. The results are given as brightness (standard deviation in parentheses) for the experiment according to the invention and for the control experiment, and the increase in brightness is calculated.

	Type of newspaper	Printed fine	Regular
	Aging time	8 months	4 months
15	Invention	57.9 (0.4)	38.3 (0.3)
	Control	54.8 (0.8)	36.6 (0.5)
	Increase	3.1	1.7

EXAMPLE 2

Enzyme treatment before disintegration without deinking chemicals

- The same two types of old newspaper as in Example 1 were subjected to enzyme treatment, followed by disintegration, flotation and washing, as follows:
- a) The old newspaper was cut approx. to 3 x 3 square cm and 100 g (dry substance) was weighed out. The paper was mixed with 1800 ml hot water (45 °C) and enzyme solution was added. The enzyme was α-amylase (Aquazyme Ultra) at a dosage of 0.5 KNU/g of dry pulp, in 100 ml of buffer at pH 7 (Britton-Robinson, universal Buffer I).

WO 95/14807 PCT/DK94/00437

8

- b) The mixture was incubated in a plastic bag in a water bath at 50 °C for 30 min. and then disintegrated in a disintegrator at 45,000 rotations in 15 min at 45-50°C at pH 7 and pulp consistency 5%.
- c) After dilution (to 0.5% pulp consistency), the pulp was replaced to 5 flotation cell and agitated for 20 min. by mixer. Flotation conditions were 50 °C, pH 7, 10 min., 2000 rpm for air flow. Ink coming up with bubbles was scratched out.
 - d) Washing was done by taking 4 L of pulp after the flotation and washing 1 L each at 50°C, pH 7 on an 80 mesh sieve and filling up to 2.5 L.
- e) Paper sheets were made from pulp after the flotation and from pulp 10 after the washing in a conventional manner. The brightness of the paper sheets was measured in a spectrophotometer with a blue filter.

Control sheets were made by the same procedure, but without the enzyme addition. The results are given as brightness for the experiment according to the invention and for the control experiment, and the increase in brightness is calculated.

	Newspaper	Printed fine		Regular		
	Aging time	6 mc	onths	3 mc	onths	
	Brightness	After flotation	After washing	After flotation	After washing	
	Invention	62.9	68.5	46.3	52.7	
20	Control	57.2	64.9	45.1	50.9	
	Increase	5.7	3.6	1.2	1.8	

EXAMPLE 3

Enzyme treatment during and after disintegration without deinking chemicals

Old newspaper was treated in the same manner as in Example 2, except that in step b), the mixture was first disintegrated (at the same conditions) and then incubated in a plastic bag (at the same conditions). The results were as follows:

	Newspaper	Printed fine		Regular		
	Aging time	6 mc	onths	3 mc	onths	
	Brightness	After flotation	After washing	After flotation	After washing	
10	Invention	61.2	67.2	46.9	52.3	
	Control	57.5	64.0	43.7	49.3	
	Increase	3.7	3.2	3.2	3.0	

The results of the examples show a clear effect of the enzyme treatment, both before during and after the disintegration, both with and without 15 deinking chemicals and with both kinds of waste paper tested.

CLAIMS

- 1. A process for producing a papermaking pulp from starch-coated printed paper, comprising the following steps:
 - a) disintegrating the paper to produce a pulp,
- 5 b) treating with a starch-degrading enzyme before, during or after step a), and
 - c) separating ink particles from the pulp after steps a) and b).
- 2. The process according to the preceding claim wherein the enzymatic treatment is done at a pH in the range 6-10, preferably 8-10, and the starch-10 degrading enzyme is alkaline stable.
 - 3. The process according to either preceding claim wherein the starch-degrading enzyme is an α -amylase.
- 4. The process according to any preceding claim wherein the α-amylase is derived from a strain of *Bacillus*, preferably *B. amyloliquefaciens*, *B. licheniformis* 15 or *B. stearothermophilus*.
 - 5. The process according to the preceding claim wherein the enzymatic treatment is done with an amount of α -amylase in the range 0.01-10 KNU/g of dry matter.
- 6. The process of Claim 1, wherein the enzyme treatment is done before the disintegration.
 - 7. The process of the preceding claim wherein the enzyme treatment is done in the presence of a surfactant.

WO 95/14807 PCT/DK94/00437

- 8. The process of the preceding claim wherein the enzyme is an alkaline stable enzyme, preferably a *Bacillus* α -amylase, and the enzyme treatment is done in the presence of an alkaline reagent at a pH in the range 8-10, preferably 8-9.
- 9. The process of any of claims 6 8, further comprising shredding or 5 cutting of the paper before the enzyme treatment.
 - 10. The process of any of claims 6 9, further comprising bleaching after the disintegration, but before the ink separation.
 - 11. The process of any of claims 6 10, additionally comprising separation of ink particles after the enzyme treatment, but before the disintegration.
- 10 12. The process of Claim 1, wherein the enzyme treatment is done simultaneously with the disintegration.
 - 13. The process of the preceding claim wherein the enzyme treatment and disintegration are done in the presence of a surfactant.
- 14. The process of the preceding claim wherein the enzyme is an alkaline stable enzyme, preferably a *Bacillus* α -amylase, and the enzyme treatment is done in the presence of an alkaline reagent at a pH in the range 8-10, preferably 8-9.
 - 15. The process of the preceding claim, wherein the enzyme treatment is continued after the disintegration.
- 16. The process of any of claims 12 15, comprising the following 20 sequential steps after the disintegration and the enzyme treatment:

separation of ink particles,

bleaching, and

separation of ink particles.

- 17. The process of Claim 1, wherein the enzyme treatment is done after the disintegration.
- 18. The process of the preceding claim wherein the enzyme treatment is done simultaneously with bleaching.
- 5 19. The process of the preceding claim wherein the enzyme treatment and bleaching are done in the presence of hydrogen peroxide and a surfactant.
- 20. The process of the preceding claim wherein the enzyme is an alkaline stable enzyme, preferably a *Bacillus* α -amylase, and the enzyme treatment is done in the presence of an alkaline reagent, preferably at a pH in the range 8-10, 10 preferably 9-10.
 - 21. A process for making new paper from starch-coated printed paper, comprising producing a papermaking pulp by the process of any preceding claim, and making the new paper from the pulp.

International application No.

PCT/DK 94/00437

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: D21C 5/02, C12S 3/08 // D21C9/10
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: D21C, C12S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DERWENT WORLD PATENT INDEX

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 4450043 (WILLIAM J. SCHULZ), 22 May 1984 (22.05.84), abstract	1-21
A	DE, A1, 2636951 (GÜNTHER WAGNER PELIKAN-WERKE GMBH), 23 February 1978 (23.02.78), page 1, line 28 - page 2, line 5	1-21
		
A	Dialog Information Services, file 351, Derwent WPI, Dialog accession no. 003906198, WPI accession no. 84-051743/09, KAO CORP: "De-inking agent for rege- nerating waste paper contains cellulase and opt. surfactant", JP 59009299, A, 840118, 8409 (Basic)	1-21
		

X	Further documents are listed in the continuation of Box	C. X See patent family annex.
*	Special categories of cited documents:	"T" later document published after the international filing date or prior
"A"	document defining the general state of the art which is not considered to be of particular relevance	date and not in conflict with the application but cited to understan- the principle or theory underlying the invention
"E"	erlier document but published on or after the international filing date	"X" document of particular relevance: the claimed invention cannot be
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other	considered novel or cannot be considered to involve an inventive step when the document is taken alone
	special reason (as specified)	"Y" document of particular relevance: the claimed invention cannot be
″0″	document referring to an oral disclosure, use, exhibition or other means	considered to involve an inventive step when the document is combined with one or more other such documents, such combinate
"P"	document published prior to the international filing date but later than	being obvious to a person skilled in the art
i	the priority date claimed	&" document member of the same patent family
Dat	e of the actual completion of the international search	Date of mailing of the international search report
20	F-h 100F	2 8 -02- 1995
	February 1995	
Nan	ne and mailing address of the ISA/	Authorized officer
Swe	edish Patent Office	
Вох	5055, S-102 42 STOCKHOLM	Marianne Bratsberg
Fac	simile No. +46 8 666 02 86	Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No. PCT/DK 94/00437

Category* Citation of document, with indication, where appropriate, of the relevant passages Relevant to date of the control o	aim No
WO, A1, 9114819 (NOVO NORDISK A/S), 3 October 1991 (03.10.91), abstract, cited in the application	
, in the second of the second	

INTERNATIONAL SEARCH REPORT

Information on patent family members

09/02/95

International application No. PCT/DK 94/00437

	document arch report	Publication date		t family mber(s)	Publication date
US-A-	4450043	22/05/84	AU-A- CA-A- EP-A,B- JP-C- JP-B- JP-A-	1240883 1202454 0089169 1606362 2031157 58191288	15/09/83 01/04/86 21/09/83 31/05/91 11/07/90 08/11/83
DE-A1-	2636951	23/02/78	NONE		· · · · · · · · · · · · · · · · · · ·
WO-A1-	9220857	26/11/92	AU-A- BR-A- CA-A- CN-A- DE-A- EP-A- FI-D- JP-T- NO-A,D-	1793392 9206013 2103260 1068161 4137761 0584176 935067 6508663 934148	30/12/92 15/11/94 18/11/92 20/01/93 19/11/92 02/03/94 00/00/00 29/09/94 04/01/94
WO-A1-	9114819	03/10/91	AT-T- DE-D,T- EP-A,B- SE-T3- US-A-	111987 69104195 0521999 0521999 5364501	15/10/94 19/01/95 13/01/93 15/11/94

Form PCT/ISA/210 (patent family annex) (July 1992)